

Gold Series Water Softener



Control Valve

- Manufactured by Clack®
- Residential/Light Commercial Applications
- Flow Rates up to 27 gpm (15 psi drop)
- Max Backwash 27 gpm (25 psi drop)
- Electronic metered valve for on demand regeneration
- Meter Accuracy Range: .25 - 27 GPM +/- 5 %
- Meter Capacity Range: 20-50,000 gallons
- LCD Display with 48 hours of internal power backup capacitor
- Valve body is Noryl plastic
- Operating pressures = 20-125 psi
- Operating Temperatures = 40° -110° F
- Height from top of tank = 7 3/8"
- Electrical Supply: 120V/60 HZ
- By-pass included
- 5-Year Limited Warranty

Material: Resin

- Cation Exchange (ionic form = Na)
- 52 lbs/CF
- Very high whole beaded count
- Physically hard
- Chlorine resistant



Tank

- Size: 10" x 47" (other sizes available)
- Capacity: 2.02 CF (varies with size)
- Fiberglass tank with base
- Constructed of durable composite resin
- Inner shell of polyethylene
- Corrosion resistant
- 2.5" Threaded Inlet
- Maximum Operating Pressure: 150 psi
- Maximum Operating Temperature: 120° F
- 10-Year Warranty



Brine Tank

- Size: 14" x 14" square x 34" tall (other sizes available)
- Safety Float
- Blue Polyethylene
- 5 year warranty on the tank
- 1 year warranty on the internal mechanisms

HYDROPURE
Water Treatment, LLC

Phone: 860-537-1949
Email: info@hydro-pure.com
Website: www.hydro-pure.com

Hydro-Pure Water Treatment, LLC
P.O. Box 551
Colchester, CT 06415