

Gold Series Twin Water Softener



Control Valve

- ◆ Manufactured by Clack®
- ◆ Residential/Light Commercial Applications
- ◆ Flow Rates up to 28 gpm (15 psi drop)
- ◆ Max Backwash 27 gpm (25 psi drop)
- ◆ Electronic metered valve for on demand regeneration
- ◆ Meter Accuracy Range: .25 - 27 GPM +/- 5 %
- ◆ Meter Capacity Range: 20 - 50,000 gallons
- ◆ LCD Display with 12+ hours of internal power backup capacitor
- ◆ Valve body is Noryl plastic
- ◆ Operating pressures = 20 - 125 psi
- ◆ Operating Temperatures = 40° - 110° F
- ◆ Height from top of tank = 7 3/8"
- ◆ Electrical Supply: 120V/60 HZ
- ◆ By-pass included
- ◆ 5-Year Limited Warranty



Tanks

- ◆ Size: 10" x 54" (other sizes available)
- ◆ Capacity: 2.19 CF (varies with size)
- ◆ Fiberglass tank with base
- ◆ Constructed of durable composite resin
- ◆ Inner shell of polyethylene
- ◆ Corrosion resistant
- ◆ 2.5" Threaded Inlet
- ◆ Maximum Operating Pressure: 150 psi
- ◆ Maximum Operating Temperature: 120° F
- ◆ 10-Year Warranty

Material: Resin

- ◆ Cation Exchange (ionic form = Na)
- ◆ 52 lbs/CF
- ◆ Very high whole beaded count
- ◆ Physically hard
- ◆ Chlorine resistant

Brine Tank

- ◆ Size: 18" x 33" round x 34" (other sizes available)
- ◆ Safety Float
- ◆ Blue Polyethylene
- ◆ 5 year warranty on the tank
- ◆ 1 year warranty on the internal mechanisms

HYDR**PURE**
Water Treatment, LLC